

EN12094 Extinguishing Call Points Indoor and outdoor



General Information

This range of EN12094-3:2003 approved conventional extinguishing call points is ideal for use with integrating gas extinguishing systems for the protection of high value assets in both commercial and industrial markets.

The call points can be used as part of a system to efficiently manage the release of any extinguishing gas in accordance with EN12094-3:2003.

The conventional range of call points is designed for indoor (IP24D) and outdoor (IP67) applications making it suitable for a broad range of installation environments where water and dust are likely to be present.

General Features

- First-fix functionality saves commissioning time
- Easy cable access simplifies installation
- Range of installation options, for indoor (IP24D) and outdoor (IP67) applications
- Independently verified by Bureau Veritas to EN12094-3:2003
- High quality materials maximize operational life
- Modern aesthetics and compact design with anti-tamper features

A new class of Fire Detection

Technical Specifications



Part Number	509.030.113	509.030.115	509.030.114	509.030.116
Function marketing	Manual Release	Emergency Stop	Manual Release	Emergency Stop
Range of use	Indoor	Indoor	Outdoor	Outdoor
Mounting	Surface	Surface	Surface	Surface
Operating temperature range	-10°C to 55°C	-10°C to 55°C	-25°C to 70°C	-25°C to 70°C
Relative humidity	93% +3% non condensing	93% +3% non condensing	93% +3% non condensing	93% +3% non condensing
Ingress protection	IP24D	IP24D	IP67	IP67
Maximum voltage	30 VDC	30 VDC	30 VDC	30 VDC
Current rating (switch only)	2 Amps	2 Amps	2 Amps	2 Amps
Cable termination	0.5-2.5 mm ²	0.5-2.5 mm ²	0.5-2.5 mm ²	0.5-2.5 mm ²
Materials	PC/ABS	PC/ABS	PC/ABS	PC/ABS
Dimensions				

Product Order Codes

- 509.030.113** Extinguishant release MCP EN12094
- 509.030.114** Extinguishant release WCP EN12094
- 509.030.115** Extinguishant abort MCP EN12094
- 509.030.116** Extinguishant abort WCP EN12094
- 515.001.127** Deformable FC400 MCP element
- 515.001.119** Spare glasses for manual call point (pack of 5)
- 515.001.128** Manual Call Point Plastic Hinged Cover
- 515.001.045** Spare manual call point keys (pack of 10)

Connection Details

