



TWM-1886 Wireless Repeater allows the wireless network area to be expanded by connecting to the coordinator or another repeater. It is mainly used to increase the communication distance between the wireless coordinator and wireless devices.

It is suitable for use with both TWM-1885 Wireless Addressable Coordinator and the TWM-3885 Wireless Conventional Coordinator.

| Technical Specifications | TWM-1886 |
|--|------------------------------------|
| Standard | EN54-18, EN54-25 |
| Operating Frequency | 868 mHz |
| RF Power | 14 dBm (25 mW) |
| Number of Channel | 10 |
| Number of Consecutive Router Connections | 4 |
| Total Number of Single Router Connections | 5 |
| Total Wireless Device Support | 31 (26 Device and 5 Router) |
| Coverage | 500mt (Açık Alan) |
| Programming | Onboard Control Buttons |
| Consumption | 10mA |
| Operating Temperature | -10°C ~ 55°C |
| Dimensions (mm) | 150 x 110 x 42 mm Antenna: 70mm |
| Weight | 185gr |
| Humidity | 95% RH |
| Protection Class | IP65 |

- EN 54-18 and EN 54-25 CertifiedFully Compatible with TWM-1885 and TWM-3885 Coordinators
- External Power 18-35 VDC
- Easy and Fast Installation, Commissioning and Usage
 Approx. 500mt Wireless Coverage (Open Area)

