

AT-6 / AT-25

The AT attenuator series by LDA is composed of two models that cover power ratings up to 50W@100V. They are designed for high-impedance public address lines of 70 or 100V.

All models have compatible support with various front casing models, making them interchangeable.

As an installation accessory, the surface mount box model (MC20E03) is offered, which has one installation slot.



Features:

- High impedance line attenuators
- 10 volume steps of 3dB
- Override for priority or emergency input (even at the mute position)
- Bracket compatible with different cases
- Operation input for system's emergency or priority

Technical Specifications:

MODEL	AT-6 / AT-25
Reference	LDAAT60S02 / LDAAT25S01
Line input	70 / 100V
Step attenuators	10 x -3dB
Deactivation control signal	24V DC 20 mA max
Connectors	Euroblock with easy insertion, fixed with screws
Cable (mm2)	0,14 – 1,5
Material	ABS
Color	White RAL 9003

MODEL	AT-6
Reference	LDAAT60S02
Maximum power	12W @100V, 6W @70V
Dimensions (wide x high x depth)	80,1 x 80,1 x 35 mm
Mounting	Panel, superficial box or universal box

MODEL	AT-25
Reference	LDAAT25S02
Maximum power	50W @100V, 25W @70V
Dimensions (wide x high x depth)	80,1 x 80,1 x 54 mm
Mounting	Panel or superficial box

AT-6 / AT-25**Accessories:****Mount box MC20EC03****Enclosures**