




SIMPLICITY.
APPLIED.

UNIVERSAL COMMERCIAL FIRE COMMUNICATOR

5G READY
now with
LTE-M
RED
EN54-21



MQ03-LTE-M-EN54



FUTURE-PROOF TECHNOLOGY

Dual-SIM device, each SIM supporting multiple operators per country



FAST AND EASY INSTALLATION

with any panel using Contact ID, SIA and Pulse 4+2



RELIABLE DATA REPORTING

to any Alarm Receiving Center



IMPROVED RECURRING REVENUE

Low flat-rate monthly fees for improved profitability



SIMPLICITY.
APPLIED.

MAIN FEATURES

REPORTING FORMATS – Dial Capture Interface supporting Contact ID, SIA and Pulse 4+2

EXCEPTIONAL REDUNDANCY – Dual-SIM device, each SIM supporting multiple operators per country

SUPERVISED CONNECTIVITY – 10 minute polling of the connection

ADMIN PORTAL – Online 24/7 device management & real-time status monitoring of user accounts

FULL EVENT REPORTING – Reliable reporting to any Alarm Receiving Center

INSTALLER MOBILE APP – Real-time on-site communication diagnostics and device configuration

UNIVERSAL PANEL COMPATIBILITY – Support of any panel via dial capture interface or digital inputs

SPECIFICATIONS

- Multi-band CAT-M1 LTE
700/850/1700/1900/2100 MHz
- Dial Capture Interface: CID, SIA, Pulse 4+2
- 4 inputs & 2 outputs (programmable)
- Supply voltage: +12 to +29 VDC
- Consumption: Standby 50mA, Peak 200mA
- Dimensions: 63 x 90 x 32 mm
- Weight: 73g without antenna

CERTIFICATIONS

- EN54-21
- RED

RCONTROL ADMIN MOBILE APP

