

PowerG + Indoor PIR Cam

The Next Generation of Motion



Improved Image Quality View high-resolution color images and video clips in

real time through the Alarm.com app.



Extended Camera Range

Ensure full coverage of rooms, hallways and stairways for enhanced security and peace of mind.



Fast Alarm Verification

Provide real time visual alarm verification to central stations when the PIR Cam detects motion.



Pet Immunity

Get more accurate notifications with an optional pet immunity configuration that reduces false alarms.



Flexible Power Options Choose wired or battery-operated wire-free

installation to fit home or business needs.



Two-Factor Authentication

Enroll devices using a PIN code when connecting to panels compatible with PowerG +.









SPECIFICATIONS	
Operating Frequencies	433,868,915MHz
Coverage	12 x 12m (40 x 40ft) / 90°
Battery Type	2 x 3V lithium CR-123A
Battery Life	5 years with typical use in room temperature
Mounting Height	1.8 to 2.4m (6 - 8ft) - PIR 1.8 to 2.1m (6 - 7ft) - Pet-tolerant
RF/Radia Technology	PowerG
Dimensions	125 × 63 x 60mm (4.9 x 2.5 x 24in)
Weight (With battery)	200g (70z)
Operating Temperature	-10° - 50°C (14° - 122°F)
Tamper Protection	Front cover and back
Compliance	EN 50131-1 Grade 2 Class II, EN 50131-2-2 (Europe) CFR 47 Part 15 (USA) Industry Canada
Optional Accessories	Wall, corner and ceiling brackets
FCC Certification (912 to 919 MHz)	47CFR part 15.427
ISED Certification (912 to 919 MHz)	RSS-247
UL/ULC Certification	UL 639, ULC + 306
Compatibility	IQ Panel 4, IQ4 Hub, IQ4 NS (PowerG +) IQ Pro, DSC PowerSeries NEO and PowerSeries Pro (Legacy/Fallback)
Part Number	PGP9934P

CAMERA SPECIFICATIONS	
CMOS	
12m (40ft) in daytime; 10m (33ft) in complete darkness	
Color/B&W: QVGA (320 x 240 pixels)	
QQVGA (160 x 120 pixels)	
HD (1280 × 720 pixels, Peek-In only)	
VGA (640x480 pixels)	
Up to 2 frames per second	
Wide angle 90°	
Instant capture functionality	

Pattern









