



## 48-Port Shielded Blank Patch Panel, 1U

Unloaded 19-inch Rackmount Keystone Panel for High-density Installations, Removable Cable-Management Bar, Black

Part No.: 721028

EAN-13: 0766623721028 | UPC: 766623721028

### Modular 19-inch 1U 48-Port Shielded Blank Patch Panel for Keystone Jacks - Maximize Connectivity in Minimal Space

With its slim 1U installation height, this rack-mount blank patch panel provides you with more connectivity options in limited rack space. The numbered ports seamlessly accommodate keystone jacks and offer easy device identification. A removable cable-management bar helps keep cables in place. The included grounding wire shields your valuable equipment from external electrical surges to ensure the longevity of your network infrastructure. Construction from sturdy, high-quality, cold-rolled SPCC steel guarantees reliability for many years. A cage nut set with four cage nuts, four M6 screws and four plastic washers are included to make your installation easier. This patch panel supports voice, data, audio, video, and fiber-optic distribution. It is ideal for a wide range of applications in small to medium-sized businesses, making it an excellent choice for IT professionals in various industries.

#### Features:

- Rackmount blank patch panel with numbered ports to accommodate shielded and unshielded keystone jacks
- 48 ports using only 1U of rack space for more connectivity
- Removable cable-management bar
- Earthing kit included to protect equipment from external electrical surges
- Sturdy, high-quality, cold-rolled SPCC steel construction
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm rack-mount equipment
- Includes 19" mounting material with four cage nuts, four M6 screws and four plastic washers

- Designed to support the distribution of voice, data, audio, video and fiber optic needs for commercial or residential applications
- Lifetime warranty

## Specifications:

### Standards and Certifications

- CE
- RoHS
- REACH
- UKCA
- ANSI/EIA 310-E
- IEC 60297-3

### Physical

- Dimensions (D x W x H): 121 x 482.6 x 44.4 mm (4.76 x 19 x 1.75 in.)
- Net weight: 570 g (1.26 lbs.)
- Gross weight: 620 g (1.37 lbs.)
- Earthing cable length: 30 cm (11.8 in.)

### Environmental

- Operating temperature: -10 - 60°C (14 - 140°F)
- Storage temperature: -40 - 70°C (-40 - 158°F)
- Operating humidity (non-condensing): 10 - 90% RH

### Package Contents

- 48-Port Shielded Blank Patch Panel, 1U
- Earthing kit
- Cage nut set (4 x cage nut, 4 x M6 screw, 4 x plastic washer)

This product is part of a group; the complete list of variations follows:

- #721011 - 24-Port Shielded Blank Rack-Mount Patch Panel, 0.5U
- #721028 - 48-Port Shielded Blank Rack-Mount Patch Panel, 1U



