

DNAKE 280SD-R2

Instruction

The DNAKE 280SD-R2 enables you to make the video call with villa entrance door, and open the door remotely from indoor monitor or mobile APP. It also makes an easy integration with SIP devices and lift control system.



Key Features

- Powered by PoE or power adapter (DC12V/2A)
- Open the door by IC card (20,000 users)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Easy integration with elevator control system

Physical

- | | |
|--|---|
| • System: Linux | • RS485 Port: 1 |
| • RAM: 64 MB | • Relay Out: 1 |
| • ROM: 128 MB | • Exit Button: 1 |
| • Front Panel: Plastic | • Door Magnetic: 1 |
| • Power Supply: PoE (802.3af) or DC 12V/2A | • IP Rating: IP65 |
| • Standby Power: 1.5 W | • Installation: Surface mounting |
| • Rated Power: 3 W | • Dimension: 170.5 x 111 x 38.6 mm |
| • Camera: 2MP, CMOS | • Working Temperature: -40°C to +55°C |
| • Ethernet Ports: 1 x RJ45, 10/100 Mbps adaptive | • Storage Temperature: -40°C to +70°C |
| • Door Entry: IC card (13.56MHz), NFC | • Working Humidity: 10% to 90% (non-condensing) |



Datasheet

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing angle: 100° (D)
- Max. Image Transfer Rate: 1080p – 30fps
- Light Compensation: LED white light

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE 280SD-R2
(Power adapter not included)
 - Screwing kit
 - Quick Start Guide
- Qty/CTN: 12 pcs
- N.W/PCS: 0.42 kg
- G.W/CTN: 8.42 kg
- Giftbox Size: 255 x 165 x 80 mm
- Carton Size: 450 x 480 x 285 mm

