


# 360° Panoramic H.265+ Fisheye Network Camera




**IP67**
**IK10**
**DATASHEET**

## KEY FEATURES

- ▶ **Smart Stream** (Bandwidth, storage and bit rate are saved with Smart Stream On, eg, H.265+ saves 70%~80% bandwidth that of H.264.)
- ▶ **User-friendly Interface Design** (Three different installation modes to choose including "Ceiling", "Wall" and "Flat".)
- ▶ **Powerful Dewarp Capability** (Dewarping the original Fisheye View into other display modes while remaining the high image quality.)
- ▶ **Multi-interface** (Easy installation with built-in Microphone, Audio I/O, Alarm I/O and DC12V.)
- ▶ **120dB Super WDR** (Excellent performance even when the ratio of the luminosity of brightest and darkest is up to 120dB.)
- ▶ **256G** (Supporting ultra-large external microSD/SDHC/SDXC card storage up to 256G.)
- ▶ **Video Content Analysis** (With 10 detection modes, VCA greatly enhances the performance bringing comprehensive surveillance functions.)

### Two Kinds of Compatible Modes

Milesight Fisheye Camera offers Bundle-Stream Mode and Multi-Channel Mode to meet different needs. The Bundle-Stream Mode combines all the channels into one and sends to NVR or VMS, which is easy for compatibility. The Multi-Channel Mode sends all the original channels to NVR or VMS, so the channels can be modified separately.



### 5/12MP Ultra High Resolution


Fisheye Network Camera features with up to 5/12MP ultra high resolution better restoring the images to guarantee superb image quality. The camera is a special model which produces spherical image and will have the dewarp process to adjust the original images to fit human eyes. The process may cause the pixel losing. That is why the high resolution is vital for a fisheye camera.

### 360° Panoramic Experience

The camera could easily reach the effect of over 4 regular network cameras with higher efficiency. Bringing 360° surround view with zero blind spots, it is able to provide comprehensive coverage of open areas such as airports, shopping malls, parking lots, retail stores, offices and more.



# 360° Panoramic H.265+ Fisheye Network Camera




## Stunning H.265+ Codec

Milesight H.265+ Series network cameras with the latest H.265+ compression codec reduce 70%~80% of bandwidth occupancy compared with H.264 while maintaining high visual quality, which boost the overall capacity of cameras.

## Smart IR II Technology

The Smart IR II Technology has been upgrade to provide videos with a viewing range of up to 15m. The advanced IR technology allows even IR light distribution in different situation and the brightness can be adjusted manually. Moreover, with the IR anti-reflection panel, the infrared light transmittance is highly increased.




## Exquisite Design

The body design of the camera insists on the idea of neatness and exquisiteness. As a whole, the screw-free design and Multiple-interface Cable keep the body neat. The Power Supply Board replaced the traditional way of power supply with cable which freeing interior space, making the camera an art of surveillance inside and out.

## Robust & Reliable Performance

Featuring IP67 Weather-proof and IK10 Vandal-proof, the camera shields its sensitive electronics from dust and water, which ensures stable operation in all weather conditions. Also protect itself from the unexpected violence, guaranteeing the smooth running to avoid potential damages.



# 360° Panoramic H.265<sup>+</sup> Fisheye Network Camera



	Model	MS-C5374-PB (5MP)	MS-C9674-PB (12MP)
<b>Camera</b>	Image Sensor	1/2.8" Progressive Scan CMOS	1/1.7" Progressive Scan CMOS
	Min. Illumination	Color: 0.005Lux@F1.2 Color: 0.008Lux@F2.0 B/W: 0Lux with IR on	Color: 0.01Lux@F1.2 Color: 0.05Lux@F2.8 B/W: 0Lux with IR on
	WDR	120dB Super WDR	
	Lens	1.25mm@F2.0	1.98mm@F2.8
	Mount	M12	
	Field of View	Ceiling Mount: 360°; Wall Mount: 180°; Flat Mount: 360°	
	Shutter Time	1/100000s~1s	
	IR Distance	Up to 15m	
	Day/Night Mode	Day/Night/Auto/Customize/Schedule	
	S/N	>55dB	
<b>Video</b>	Max. Image Resolution	2592x1944	4000x3000
	Primary Stream	Fisheye View: 30fps@(2592x1944, 1944x1944, 1536x1536, 1280x1280)	Fisheye View: 25fps@(4000x3000), 30fps@(3000x3000, 2560x2560, 1920x1920, 1280x1280)
	Secondary Stream	Fisheye View: 30fps@(1280x960, 1024x1024, 720x720, 320x320)	
	Video Compression	H.265 <sup>+</sup> /H.265(HEVC)/H.264 <sup>+</sup> /H.264	
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	
	Privacy Masking	Up to 8 areas	
	ROI	Up to 8 areas	
	Image Setting	Brightness/Contrast/Saturation/Sharpness	
<b>Display</b>	Mount Mode	Ceiling Mount/Wall Mount/Flat Mount	
	Decoding Mode	On-board Dewarping/Client-side Dewarping	
	Display Mode	<b>11 display modes in total</b> <b>Client-side Dewarping:</b> Ceiling Mount: 1O, 1P, 2P, 4R, 1O3R, 1P1R, 1P4R, 1P6R, 1O8R Wall Mount: 1O, 1P, 4R, 1O3R, 1P1R, 1P4R Table Mount: 1O, 1P, 2P, 4R, 1O3R, 1P1R, 1P4R, 1P6R, 1O8R <b>On-board Dewarping:</b> Ceiling Mount: 1O, 1P, 2P, 4R, 1O3R, 1P3R, 1O1P3R Wall Mount: 1O, 1P, 4R, 1O3R, 1P3R, 1O1P3R Table Mount: 1O, 1P, 2P, 4R, 1O3R, 1P3R, 1O1P3R  Note: 1. Only Fisheye in Multi-Channel Mode supports 1O1P3R. 2. The above letters O, P and R are explained as follows: O----Fisheye View; P----180° Fisheye View; 2P----360° Fisheye View; R----PTZ	
<b>Interface</b>	Ethernet	1*RJ45 10M/100M Ethernet Port	1*RJ45 10M/100M/1000M Ethernet Port
	Audio I/O	Built-in Microphone	Built-in Microphone and Audio Input/Output interface
	Alarm I/O	N/A	1/1
<b>Network</b>	Network Storage	NAS(Support NFS, SMB/CIFS), ANR	
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
<b>Audio</b>	Audio Compression	G.711/AAC/G.722/G.726	
	Audio Sampling Rate	8/16/32/48KHz	
	Audio Bit Rate	16~256kbps	
	Two-way Audio	Support	

# 360° Panoramic H.265<sup>+</sup> Fisheye Network Camera




<b>System</b>	Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G	
	Advanced Function	Auto Tracking, Heat Map, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark	
	SIP/VoIP Support	Yes, Voice & Video-over-IP	
	Event Trigger	Motion Detection, Network Disconnection, Audio Alarm, etc.	Motion Detection, Network Disconnection, Audio Alarm, External Input, etc.
	Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc.
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed	
	System Compatibility	ONVIF Profile G & Q & S & T, API	
<b>General</b>	Working Temperature	-40°C~60°C	
	Working Humidity	0~90%(Non-condensing)	
	Power Supply	PoE (802.3af) / DC 12V±10%	
	Power Consumption	4.2W MAX 6.6W MAX (With IR on)	4.8W MAX 8W MAX (With IR on)
	Housing	Vandal-proof IK10-rated Metal Housing / Up to IP67-rated for Weather-resistant Performance	
	Weight	1100g	
	Dimensions	Φ140mmX45.4mm	
	Warranty	3/5 Years	


# 360° Panoramic H.265+ Fisheye Network Camera




## Structure Diagrams



## 5MP Fisheye Camera



## 12MP Fisheye Camera



Units: mm

## Accessories Support

### A01 Pole Mount

Weight: 720g  
Dimensions: 170\*51.5\*152.6mm



### A03 External Corner Bracket

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



### A72 Wall Mount

Weight: 560g  
Dimensions: 240\*160\*136mm



### A75 Junction Box

Weight: 200g  
Dimensions: 155.5\*167\*33.5mm



### A76 Pendant Mount

Weight: 620g  
Dimensions: 136\*L (L is default as 300mm, also can be extended with A76-L)



### A76-L Extension Lever

Weight: 315g  
Dimensions: 34\*300mm



Milesight Technology Co.,Ltd. | [www.milesight.com](http://www.milesight.com)

Contact Us: [sales@milesight.com](mailto:sales@milesight.com) [support@milesight.com](mailto:support@milesight.com)



Add: 220 NE 51st Street, Oakland Park, Florida 33334, USA  
Tel: +1-800-561-0485

Add: 925, Anyang SK V1 Center, LS -ro 116beon-gil, Dongan-gu, Anyang-si, Korea  
Tel: +82-31-990-7732

Add: No.23 Wanghai Road, 2nd Software Park, Xiamen, China  
Tel: +86-592-5922772

