# IPC\_D1203-B0003P72D1812 Release Notes

Zhejiang Uniview Technologies Co., Ltd

# IPC\_D1203-B0003P72D1812

## **Release Notes**

Keywords: Version information, version upgrade

Abstract: This document provides detailed version information and upgrade procedure for

IPC\_D1203-B0003P72D1812.

#### Acronym:

| Acronym | Full Name |
|---------|-----------|
| IPC     | IP Camera |

# Content

| 3 |
|---|
| 3 |
|   |
| 3 |
| 3 |
| 3 |
| 8 |
| 8 |
| 8 |
| 8 |
| 9 |
| 9 |
| 9 |
|   |

## 1 Version Information

#### 1.1 Version Number

IPC\_D1203-B0003P72D1812

## 1.2 Release History

#### Table1Released versions

| Version No.             | Basic Version No.       | Released On | Remarks          |
|-------------------------|-------------------------|-------------|------------------|
| IPC_D1203-B0003P72D1812 | IPC_D1203-B0003P71D1812 | 2021-07-19  | Improved release |

#### Table2 Version mapping table

| Product Mapping Item | Version No. (For External) |
|----------------------|----------------------------|
| NVR                  | B3328P36                   |

## 1.3 Version Mapping Table

Table3Product models and corresponding versions

| Product Series   | IPC Series  |  |  |
|------------------|---|--|--|
| Series           | IPC2122LR3、IPC3612LR3、IPC322LR3、IPC2C22LR6、IPC  |  |  |
|                  | IPC2122LR3series:IPC2122LR3-PF40-E、IPC2122LR3-PF60-E、IPC2122LR3-F40-E   |  |  |
|                  | IPC3612LR3series: IPC3612LR3-PF40-E、IPC3612LR3-PF28-E、IPC3612LR3-F28-E  |  |  |
|                  | IPC322LR3series: IPC322LR3-VSPF28-E \ IPC322LR3-VSPF40-E \ IPC322LR3-VSF28-E  |  |  |
| Models           | IPC2C22LR6 series:IPC2C22LR6-F40-E、IPC2C22LR6-PF40-E、IPC2C22LR6-PF60-E  |  |  |
|                  | IPC series: IPC-B112-PF28、IPC-B112-PF40、IPC-D112-PF28、IPC-D112-PF40、IPC-T112-PF28、IPC-T112-PF40、IPC-B113-PF28、IPC-B113-PF40、IPC-D113-PF28 IPC-D113-PF40、IPC-T113-PF28、IPC-T113-PF40、IPC-B122-PF28、IPC-B122-PF40 IPC-T122-PF28、IPC-T122-PF40、IPC-B122-PF28-SC、IPC-B122-PF40-SC IPC-T122-PF28-SC、IPC-T122-PF40-SC |  |  |
| Target file name | IPC_D1203-B0003P72D1812.zip   |  |  |

# 2 Feature Change Description

P72D1812:

None

P71D1812:

None

#### P70D1812:

| Item                 | Feature             | Description   |
|----------------------|---------------------|---|
| Newly added features | New added<br>models | IPC-B122-PF28-SC、IPC-B122-PF40-SC、IPC-T122-PF28-SC、IPC-T122-PF40-SC |
| Improved<br>features | None                | None  |
| Deleted<br>features  | None                | None  |

P67D1812:

None

P66D1812:

| Item                 | Feature             | Description  |
|----------------------|---------------------|--|
| Newly added features | New added<br>models | IPC-B122-PF28、IPC-B122-PF40<br>IPC-T122-PF28、IPC-T122-PF40 |
| Improved<br>features | None                | None   |
| Deleted<br>features  | None                | None   |

P63D1812:

None

P62D1812:

| ltem                    | Feature          | Description   |
|-------------------------|------------------|---|
| Newly added<br>features | New added models | IP camera requires a strong password  1. After default password is entered at first login, a pop-up window leads the user to change the password, and only accepts a strong password.  2. Requires the user to change password if a weak or medium password is used to login.  3. A strong password is required when changing password.  4. Friendly password mode is removed.  5. A strong password shall include at least nine characters comprising all three types: digits, letters, and special characters. Both uppercase and lowercase letters are supported.  6. The default password changes to 123456 (admin was supported previously).  IPC322LR3-VSF28-E、IPC3612LR3-F28-E |
| Improved<br>features    | None             | None  |
| Deleted<br>features     | None             | None  |

P60D1812:

None

P35D1812:

| ltem                 | Feature           | Description  |
|----------------------|-------------------|--|
| Newly added features | New added models: | IPC-B113-PF28、IPC-B113-PF40、IPC-D113-PF28<br>IPC-D113-PF40、IPC-T113-PF28、IPC-T113-PF40 |
| Improved features    | None              | None   |
| Deleted<br>features  | None              | None   |

#### P30D1812:

| ltem                 | Feature | Description  |
|----------------------|---------|--|
| Newly added features | None    | None   |
| Improved features    | Log     | Includes IR cut switch count in logs to facilitate judgment on its service life. |
| Deleted<br>features  | None    | None   |

#### P20D1812:

| Item                 | Feature           | Description   |
|----------------------|-------------------|---|
| Newly added features | New added models: | IPC-D112-PF28、IPC-D112-PF40、IPC-T112-PF28、IPC-T112-PF40 |
| Improved             | None              | None  |
| Deleted<br>features  | None              | None  |

#### P10D1812:

| Item        | Feature                     | Description   |
|-------------|-----------------------------|---|
|             | Illegal login lock          | Add illegal login lock on the Web interface. When enabled,        |
|             |                             | the account will be locked after 5 consecutive wrong              |
|             |                             | passwords.  |
|             | NTP server port             | NTP server port configurable.                                     |
| Newly added | SDDP                        | Add <b>SDDP</b> and <b>Identify</b> settings in <b>Demo</b> page. |
| features    | Refresh <b>Storage</b> page | Storage page refreshes after the storage medium is                |
|             |                             | formatted.  |
|             | English/Chinese             | Distribution products support English/Chinese language            |
|             | language                    | switch.   |
|             | New added models            | IPC-B112-PF28、IPC-B112-PF40                                       |
| Improved    | Streams                     | For E model device, the maximum number of streams                 |
| features    |                             | changes from 4 to 8.  |
| Deleted     | None                        | None  |
| features    | INOTIE                      | NOTIE   |

P30D1809:

None

#### P20D1809:

| Item        | Feature          | Description                        |
|-------------|------------------|------------------------------------|
| Newly added | New added models | IPC2C22LR6-F40-E、IPC2C22LR6-PF40-E |
| features    |                  | IPC2C22LR6-PF60-E                  |
| Improved    | None             | None                               |
| features    | None             | None                               |
| Deleted     | Nana             | None                               |
| features    | None             | None                               |

#### P10D1809:

| Item                    | Feature  | Description  |
|-------------------------|--|--|
| Newly added<br>features | Alarm report to EZVMS over WAN                     | Alarm report to EZVMS over the WAN.  |
|                         | Old password<br>required when<br>changing password | Old password is required when changing user password.  |
|                         | SSL certificate signature algorithm change         | The signature algorithm for SSL certificate changes from SHA-1 to SHA-2.   |
|                         | Open source software licenses                      | Add open source software licenses on the Basic Info page of Web interface.   |
| Improved<br>features    | Record IP and port of operation source in logs     | When configuring or managing IPC on platform, NVR or IPC Web interface, the IP address and port number of the operation source will be recorded in IPC logs. |
| Deleted<br>features     | None   | None   |

# 3 Version Upgrade Description

None.


# 4 Version Upgrade Procedure

## 4.1 Upgrade Overview

## 4.1.1 Version Upgrade Environment

1. Network Architecture for Upgrade

Figure1Network architecture



As shown in this figure, the version files are stored on the PC that is connected to the IPCs through the network.


#### 4.1.2 Version Upgrade Modes

You can upgrade through the Web.

#### 4.2 Upgrade Procedure

#### 4.2.1 Upgrade Through the Web

- (1) Log in to the Web interface as **admin** (default password: 123456).
- (2) Click Setup>Maintenance>Device Maintenance. The Device Maintenance page is displayed.



- (3) Click **Browse** in the **Firmware Upgrade** area. In the **Select** dialog box that appears, select the upgrade file package, for example, IPC\_D1203-XXXXX.zip, and then click **Open.**
- (4) Click **Upgrade**. You cannot operate on other pages during the upgrade process.
- (5) Wait till the upgrade is completed. A message appears to indicate successful upgrade and prompt you to log in again after the device restarts.

 $@\ 2014-2021, Zhejiang Uniview\ Technologies\ Co.,\ Ltd. All\ Rights\ Reserved.$ 

No part of this manual may be reproduced or transmitted in any form or by any means without priorwritten consent of Zhejiang Uniview Technologies Co., Ltd.

The information in this manual is subject to change without notice.